




Features

- 3/8" Square/ Multiturn / Cermet / Industrial / Sealed
- Five popular terminal styles
- Standoffs
- Patent #4427966 drive mechanism

3299 - 3/8" Square Trimming Potentiometer

Electrical Characteristics

Standard Resistance Range
.....10 to 2 megohms
(see standard resistance table)

Resistance Tolerance $\pm 10\%$ std.
(tighter tolerance available)

Absolute Minimum Resistance
.....1% or 2 ohms max.
(whichever is greater)

Contact Resistance Variation
.....1.0% or 3 ohms max.
(whichever is greater)

Adjustability
Voltage $\pm 0.01\%$
Resistance $\pm 0.05\%$

Resolution Infinite

Insulation Resistance500 vdc.
1,000 megohms min.

Dielectric Strength
Sea Level900 vac
70,000 Feet350 vac
Effective Travel25 turns nom.

Environmental Characteristics

Power Rating (300 volts max.)
70°C0.5 watt
125°C0 watt

Temperature Range-55°C to +125°C

Temperature Coefficient ± 100 ppm/°C

Seal Test85°C Fluorinert*

HumidityMIL-STD-202 Method 103
96 hours
(2% Δ TR, 10 Megohms IR)

Vibration20G (1% Δ TR; 1% Δ VR)

Shock100G (1% Δ TR; 1% Δ VR)

Load Life
.....1,000 hours 0.5 watt @ 70°C
(3% Δ TR; 3% or 3 ohms,
whichever is greater, CRV)

Rotational Life200 cycles
(4% Δ TR; 3% or 3 ohms,
whichever is greater, CRV)

Physical Characteristics

Torque3.0 oz-in. max.

Mechanical StopsWiper idles

TerminalsSolderable pins

Weight0.035 oz.

MarkingManufacturer's
trademark, resistance code,
wiring diagram, date code,
manufacturer's model
number and style

WiperSet at CW end


FlammabilityU.L. 94V-0

Standard Packaging50 pcs. per tube


Adjustment ToolH-90

3299P


Common Dimensions




3299W





3299X



3299Y



3299Z



TOLERANCES: ± 0.25 (.010) EXCEPT WHERE NOTED

DIMENSIONS ARE: $\frac{\text{METRIC}}{\text{(INCHES)}}$

Standard Resistance Table

Resistance (Ohms)	Resistance Code
10	100
20	200
50	500
100	101
200	201
500	501
1,000	102
2,000	202
5,000	502
10,000	103
20,000	203
25,000	253
50,000	503
100,000	104
200,000	204
250,000	254
500,000	504
1,000,000	105
2,000,000	205

Popular values listed in boldface. Special resistances available.

How To Order

Model **3299 W - 1 - 103**

Style _____

Standard or Modified Product Indicator
-1 = Standard Product

Resistance Code _____

Consult factory for other available options.

*"FLUORINERT" IS A REGISTERED TRADEMARK OF 3M CO.