

<b>PartNumber</b>	OS102011MS2QN1
<b>Product Family</b>	Slide Switches
<b>Product Group</b>	OS Series
<b>Product Description</b>	Miniature Slide Switches
<b>Mounting Style</b>	PC thru-hole
<b>Movable Contact Material</b>	C5210R-EH, Silver Plated or Gold
<b>Switch Function</b>	On / On, SPDT
<b>Connector Terminals</b>	1-2 / 2-3
<b>Switch Type</b>	2 Positions
<b>Housing and Base Material</b>	SPCC SnPb plated, Phenolic Resin
<b>Mode of Switching</b>	Non-shorting
<b>Insulation Resistance</b>	500 VDC for 1 minute
<b>Note</b>	Specifications and materials listed above are for switches with standard options. For information on specific and custom switches, consult Customer Service Center.
<b>Series and Sequential Number</b>	SSA, 2
<b>Contact Rating</b>	0.2A @ 30 VDC; 0.1A @ 30 VDC; 0.1A @ 12 VDC
<b>Contact Resistance</b>	20 milliohms or less
<b>Actuator Material</b>	0.4mm high plastic / POM / Black
<b>Mechanical and Electrical Life</b>	10,000 cycles
<b>Operating Temperature</b>	-10 °C to + 70 °C
<b>Dielectric Strength</b>	500 VAC for 1 minute
<b>Stationary Contact Material</b>	Brass, Silver Plated
<b>Terminal Material</b>	Brass, Silver Plated or Gold (Model Dependant)
<b>Terminal Seal</b>	None
<b>Packaging</b>	Bulk