

PARTS NUMBER SYSTEM

JAMICON®

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18
S	K	R	2	2	1	M	1	C	F	1	1	V	W	C			
SERIES		TYPE		CAPACITANCE (μ F)		CAP. TOL.		VOLTAGE (W.V.)		CASE SIZE (∅D mm)		SPECIAL REQUIREMENTS Length of Al.case					
See Page 2										Length of Al.case							
Type	Code	Cap. (μF)	Code	Tolerance (%)	Code	Voltage (w.v.)	Code	Diameter (mm)	Code								
Radial	R	0.1	0R1	+10	K	4	0G	3	A								
		0.22	R22	-10		6.3	0J	3.8	S								
		0.33	R33	+15	L	10	1A	4	C								
Radial Taping	P	0.47	R47	-15		M	13	1P	5	D							
		1	010	+20	16		1C	6	W								
		2.2	2R2	-20	20	1D	6.3	E									
Lug	W	3.3	3R3	+100	P	25	1E	7	Y								
		4.7	4R7	-0		35	1V	8	F								
		10	100	+ 30	Q	40	1G	10	G								
Screw	S	22	220	-10		R	50	1H	12	H							
		33	330	+20	63		1J	12.5	I								
		47	470	-0	T	80	1K	13	J								
		100	101	+50		100	2A	16	K								
		220	221	-10	U	125	2B	18	L								
		330	331	+75		160	2C	20	M								
		470	471	-10	V	200	2D	22	N								
		1000	102	+20		250	2E	25	O								
		2200	222	-10	H	315	2F	30	P								
		3300	332	+20		330	2U	35	Q								
4700	472	-5	F	350	2V	40	R										
10000	103	+30		400	2G	51	V										
22000	223	-0		450	2W												

Code	Description	Code	Description
V	Case Vent	W	Without Sleeve
—	Case No Vent	1 ~ 9	Customer Assign
		A ~ Z	Assign
		a ~	Brand

Code	Type	Description
P	Radial	Taping (Ammo Pack)
C		Lead Cut
F		Lead Forming Cut
B		Lead Forming Only
Y		Lead Snap in
W	Lug	Snap in Terminal
G		G Type Terminal
V		V Type Terminal
S	Screw	Screw Terminal Type