



Part No.	Material	λ D (nm)	Lens Type	Iv (mcd) @10mA *20mA		Viewing Angle	Dimension
				Min.	Typ.		
L-383HDT	GaP	660	red diffused	0.4	1	110°	2.5mm x 5mm Rectangular
L-383IDT	GaAsP/GaP	625	red diffused	3	5	110°	
L-383SRDT	GaAlAs	640	red diffused	*36	*70	110°	
L-383SRWT	GaAlAs	640	white diffused	*36	*70	110°	
L-383EDT	GaAsP/GaP	625	orange diffused	3	5	110°	
L-383YDT	GaAsP/GaP	588	yellow diffused	1	4	110°	
L-383GDT	GaP	568	green diffused	1	4	110°	
L-383SGWT	GaP	568	white diffused	*7	*15	110°	

L-714HDT	GaP	660	red diffused	0.4	1	110°	3mm x 3mm Square
L-714IDT	GaAsP/GaP	625	red diffused	3	5	110°	
L-714SRDT	GaAlAs	640	red diffused	*36	*70	110°	
L-714EDT	GaAsP/GaP	625	orange diffused	3	5	110°	
L-714YDT	GaAsP/GaP	588	yellow diffused	1	5	110°	
L-714GDT	GaP	568	green diffused	1	5	110°	

L-1553HDT	GaP	660	red diffused	0.4	1	110°	5mm x 5mm Square
L-1553IDT	GaAsP/GaP	625	red diffused	3	8	110°	
L-1553SRDT	GaAlAs	640	red diffused	*36	*80	110°	
L-1553EDT	GaAsP/GaP	625	orange diffused	3	8	110°	
L-1553YDT	GaAsP/GaP	588	yellow diffused	1	5	110°	
L-1553GDT	GaP	568	green diffused	1	5	110°	

L-503HDT	GaP	660	red diffused	0.4	1	110°	5mm x 5mm Square
L-503IDT	GaAsP/GaP	625	red diffused	3	6	110°	
L-503YDT	GaAsP/GaP	588	yellow diffused	1	3	110°	
L-503GDT	GaP	568	green diffused	1	3	110°	

DLA/6ID DLC/6ID	GaAsP/GaP	625	red diffused	12	50	120°	20mm
DLA/6SRD DLC/6SRD	GaAlAs	640	red diffused	*110	*400	120°	
DLA/6YD DLC/6YD	GaAsP/GaP	588	yellow diffused	12	50	120°	
DLA/6GD DLC/6GD	GaP	568	green diffused	18	80	120°	
DLA/6SGD DLC/6SGD	GaP	568	green diffused	*70	*200	120°	

NOTES:

1. All dimensions are in millimeters(inches).
2. Tolerance is $\pm 0.25\text{mm}(0.01")$ unless otherwise noted.