

DATA SHEET

**MBA 0204; MBB 0207;
MBE 0414
Precision leaded resistors**

Product specification
File under BCcomponents, BC08

2001 Jun 13

Precision leaded resistors

**MBA 0204; MBB 0207;
MBE 0414**

FEATURES

- Advanced thin film technology
- Low TC: ± 15 to ± 25 ppm/K
- Precision tolerance of value: $\pm 0,1\%$ and $\pm 0,25\%$
- Superior overall stability: class 0,05
- Wide precision range: 10 Ω to 1,5 M Ω
- Sizes:
 - DIN: 0204; 0207; 0414
 - CECC: A; B; D;

APPLICATIONS

- Test and measuring equipment
- Industrial electronics
- Medical electronics.

DESCRIPTION

MBA 0204, MBB 0207 and MBE 0414 precision leaded thin film resistors combine the proven reliability of the professional products with an advanced level of precision and stability. Therefore they are perfectly suited for applications in the fields of test and measuring equipment along with industrial and medical electronics.

Production is strictly controlled and follows an extensive set of instructions established for reproducibility. A homogeneous film of metal alloy is deposited on a high grade ceramic body (85% Al₂O₃) and conditioned to

achieve the desired temperature coefficient. Nickel plated steel termination caps are firmly pressed on the metallised rods. A special laser is used to achieve the target value by smoothly cutting a helical groove in the resistive layer without damaging the ceramics. A further conditioning is applied in order to stabilise the trimming result. Connecting wires of electrolytic copper plated with 100 pure tin are welded to the termination caps. The resistors are covered by protective coating designed for electrical, mechanical and climatic protection. The terminations receive a final pure tin on nickel plating. Four or five colour code rings designate the resistance value and tolerance in accordance with **IEC 60062**.

The result of the determined production is verified by an extensive testing procedure performed on 100 of the individual resistors. Only accepted products are stuck directly on the adhesive tapes in accordance with **IEC 60286-1**.

The resistors are suitable for processing on automatic insertion equipment and cutting and bending machines. They are suitable for automatic soldering using wave, reflow or vapour phase. The encapsulation is resistant to all cleaning solvents commonly used in the electronics industry, including alcohols, esters and aqueous solutions.

The resistors are tested in accordance with **CECC 40101-806** which refers to **EN 140000 (IEC 60115-1)** and **EN 140100 (IEC 60115-2)**.

BCcomponents BEYSCHLAG has achieved "**Approval of Manufacturer**" in accordance with **EN 100114-1**.

Precision leaded resistors**MBA 0204; MBB 0207;
MBE 0414****QUICK REFERENCE DATA**

DESCRIPTION	MBA 0204		MBB 0207		MBE 0414	
CECC size	A		B		D	
Resistance range	22 Ω to 332 kΩ		10 Ω to 1 MΩ		22 Ω to 1,5 MΩ	
Resistance tolerance	±0,25%; ±0,1%					
Temperature coefficient	±25 ppm/K; ±15 ppm/K					
Operation mode	precision	long term	precision	long term	precision	long term
Climatic category (LCT/UCT/days)	10/85/56	55/125/56	10/85/56	55/125/56	10/85/56	55/125/56
Rated dissipation, P_{70}	0,07 W	0,25 W	0,11 W	0,40 W	0,17 W	0,65 W
Operating voltage, $U_{\max}$ AC/DC	200 V		300 V		500 V	
Film temperature	85 °C	125 °C	85 °C	125 °C	85 °C	125 °C
Max. resistance change at P_{70} for resistance range, $\Delta R/R$ max., after:	100 Ω to 100 kΩ		100 Ω to 270 kΩ		100 Ω to 470 kΩ	
	1000 h	≤ 0,05% ≤ 0,25%	≤ 0,03% ≤ 0,15%	≤ 0,05% ≤ 0,25%		
	8000 h	≤ 0,1% ≤ 0,5%	≤ 0,1% ≤ 0,5%	≤ 0,1% ≤ 0,5%		
	225000 h	≤ 0,3% ≤ 1,5%	≤ 0,3% ≤ 1,5%	≤ 0,3% ≤ 1,5%		
Specified lifetime	225000 h		225000 h		225000 h	
Permissible voltage against ambient :						
1 minute	300 V		500 V		800 V	
continuous	75 V		75 V		75 V	
Failure rate	≤ 0,7 × 10 ⁻⁹ /h		≤ 0,3 × 10 ⁻⁹ /h		≤ 0,1 × 10 ⁻⁹ /h	

Precision leaded resistors

**MBA 0204; MBB 0207;
MBE 0414**

Table 1 Temperature coefficient and resistance range

DESCRIPTION		RESISTANCE VALUE ⁽¹⁾		
T.C.	TOLERANCE	MBA 0204	MBB 0207	MBE 0414
±25 ppm/K	±0,25%	22 Ω to 332 kΩ	10 Ω to 1 MΩ	22 Ω to 1,5 MΩ
	±0,1%	43 Ω to 332 kΩ	10 Ω to 1 MΩ	43 Ω to 1 MΩ
±15 ppm/K	±0,25%	22 Ω to 221 kΩ	10 Ω to 1 MΩ	22 Ω to 1 MΩ
	±0,1%	43 Ω to 221 kΩ	10 Ω to 1 MΩ	43 Ω to 1 MΩ

Note

1. Resistance values to be selected from E96 and E192 series, for other values please contact factory.

Resistance ranges printed in bold are preferred T.C. / tolerance combinations with optimized availability.

Precision leaded resistors

**MBA 0204; MBB 0207;
MBE 0414**

ORDERING INFORMATION

Components may be ordered by using either a simple clear text ordering code, see "Type description and ordering code" or BCcomponents' unique 12NC.

Numeric Ordering code (12NC)

- The resistors have a 12-digit ordering code starting with 2312.
- The subsequent 4 digits indicate the resistor type, specification and packaging; see Table 2.
- The remaining 4 digits indicate the resistance value:
 - The first 3 digits indicate the resistance value.
 - The last digit indicates the resistance decade in accordance with Table 3.

Table 2 12NC ordering code indicating resistor type and packaging

DESCRIPTION			ORDERING CODE 2312	
			BANDOLIER IN BOX	
TYPE	T.C.	TOL.	C1 1000 units	CT 5000 units
MBA 0204	±25 ppm/K	±0,25%	901 6....	906 6....
		±0,1%	901 7....	906 7....
	±15 ppm/K	±0,25%	902 6....	907 6....
		±0,1%	902 7....	907 7....
MBB 0207	±25 ppm/K	±0,25%	911 6....	916 6....
		±0,1%	911 7....	916 7....
	±15 ppm/K	±0,25%	912 6....	917 6....
		±0,1%	912 7....	917 7....
MBE 0414	±25 ppm/K	±0,25%	921 6....	–
		±0,1%	921 7....	–
	±15 ppm/K	±0,25%	922 6....	–
		±0,1%	922 7....	–

Resistance ranges printed in bold are preferred T.C. / tolerance combinations with optimized availability.

Table 3 Last digit of 12NC indicating resistance decade

RESISTANCE DECADE	LAST DIGIT
10 Ω to 99,9 Ω	9
100 Ω to 999 Ω	1
1 kΩ to 9,99 kΩ	2
10 kΩ to 99,9 kΩ	3
100 kΩ to 999 kΩ	4
1 MΩ to 9,99 MΩ	5

ORDERING EXAMPLE


The ordering code of a MBA 0204 resistor, value 47 kΩ and TC 25 with ±0,1% tolerance, supplied on bandolier in a box of 5000 units is: 2312 906 74703.

Precision leaded resistors

MBA 0204; MBB 0207;
MBE 0414

Type description and ordering code

- We recommend that the clear text ordering code is used to minimize the possibility of errors in order handling.



Precision leaded resistors

MBA 0204; MBB 0207;
MBE 0414

FUNCTIONAL DESCRIPTION

Derating




Fig.1 Derating, long term operation.




Fig.2 Derating, precision operation.

Precision leaded resistors

MBA 0204; MBB 0207;
MBE 0414

Temperature rise




Fig.3 Rise of the surface temperature.

Current noise




Fig.4 Current noise A_1 in accordance with IEC 60195.

Precision leaded resistors

MBA 0204; MBB 0207;
MBE 0414

MECHANICAL DATA

Outlines




Table 4 Leaded resistor types, mass and relevant physical dimensions; see Fig.5

TYPE	D _{max} (mm)	L _{max} (mm)	d _{nom} (mm)	I _{min} (mm)	M _{min} (mm)	MASS (mg)
MBA 0204	1,6	3,6	0,5	29,0	5,0	125
MBB 0207	2,5	6,3	0,6	28,0	10,0 ⁽¹⁾	220
MBE 0414	4,0	11,9	0,8	31,0	15,0	700

Note

1. For 7,5 ≤ M < 10,0 mm, use version MBB 0207 ... L0 without lacquer on the leads.

Precision leaded resistors

**MBA 0204; MBB 0207;
MBE 0414**

TESTS AND REQUIREMENTS

Essentially all tests are carried out in accordance with the following specifications:

EN 140000 / IEC 60115-1, Generic specification (includes tests)

EN 140100 / IEC 60115-2, Sectional specification (includes schedule for qualification approval)

CECC 40101-806, Detail specification (includes schedule for conformance inspection)

Most of the components are approved in accordance with the European CECC-system, where applicable. Table 5 contains only the most important tests. For the full test schedule refer to the documents listed above. The testing also covers most of the requirements specified by EIA/IS-703 and JIS-C-5202.

The tests are carried out in accordance with IEC 60068 and under standard atmospheric conditions in accordance with

IEC 60068-1, 5.3. Climatic category LCT/UCT/56 (rated temperature range: Lower Category Temperature, Upper Category Temperature; damp heat, long term, 56 days) is valid.

Unless otherwise specified the following values apply:

Temperature: 15 °C to 35 °C

Relative humidity: 45 to 75

Air pressure: 86 kPa to 106 kPa (860 mbar to 1 060 mbar).

For testing the components are mounted on a test board in accordance with IEC 60115-1, 4.31 unless otherwise specified.

In Table 5 only the tests and requirements are listed with reference to the relevant clauses of IEC 60115-1 and IEC 60 068-2; a short description of the test procedure is also given.

Table 5 Test procedures and requirements

IEC 60115-1 CLAUSE	IEC 60068-2 TEST METHOD	TEST	PROCEDURE	REQUIREMENTS PERMISSIBLE CHANGE ($\Delta R/R$)		
				STABILITY CLASS 0,05	STABILITY CLASS 0,1	STABILITY CLASS 0,25
			stability for product types:			
			MBA 0204	100 Ω to 100 k Ω	43 Ω to <100 Ω ; >100 k to 221 k Ω	22 Ω to <43 Ω ; >221 k Ω to 332 k Ω
			MBB 0207	100 Ω to 270 k Ω	43 Ω to <100 Ω ; >270 k Ω to 510 k Ω	10 Ω to <43 Ω ; > 510 k Ω to 1 M Ω
			MBE 0414	100 Ω to 470 k Ω	43 Ω to <100 Ω ; >470 k Ω to 1 M Ω	22 Ω to <43 Ω ; >1 M Ω to 1,5 M Ω
4.5	–	resistance	–	$\pm 0,25\%$; $\pm 0,1\%$		
4.8.4.2	–	temperature coefficient	at 20 / LCT / 20 °C and 20 / UCT / 20 °C	± 25 ppm/K; ± 15 ppm/K		
4.25.1	–	endurance	room temperature; $U = \sqrt{P_{70} \times R}$ or $U = U_{\max}$; 1,5 h on; 0,5 h off 70 °C; 1000 h 70 °C; 8000 h	$\pm(0,05\% + 0,01 \Omega)^{(1)}$ $\pm(0,1\% + 0,01 \Omega)$	$\pm(0,1\% + 0,01 \Omega)$ $\pm(0,2\% + 0,01 \Omega)$	$\pm(0,25\% + 0,05 \Omega)^{(2)}$ $\pm(0,5\% + 0,05 \Omega)$
4.25.3	–	endurance at upper category temperature	125 °C; 1000 h 85 °C; 1000 h	– $\pm(0,05\% + 0,01 \Omega)$	– $\pm(0,1\% + 0,01 \Omega)$	$\pm(0,25\% + 0,05 \Omega)$ –

Precision leaded resistors

MBA 0204; MBB 0207;
MBE 0414

IEC 60115-1 CLAUSE	IEC 60068-2 TEST METHOD	TEST	PROCEDURE	REQUIREMENTS PERMISSIBLE CHANGE ($\Delta R/R$)		
			stability for product types:	STABILITY CLASS 0,05	STABILITY CLASS 0,1	STABILITY CLASS 0,25
			MBA 0204	100 Ω to 100 k Ω	43 Ω to <100 Ω ; >100 k Ω to 221 k Ω	22 Ω to <43 Ω ; >221 k Ω to 332 k Ω
			MBB 0207	100 Ω to 270 k Ω	43 Ω to <100 Ω ; >270 k Ω to 510 k Ω	10 Ω to <43 Ω ; > 510 k Ω to 1 M Ω
			MBE 0414	100 Ω to 470 k Ω	43 Ω to <100 Ω ; >470 k Ω to 1 M Ω	22 Ω to <43 Ω ; >1 M Ω to 1,5 M Ω
4.24	3 (Ca)	damp heat, steady state	40 $\pm$ 2 $^{\circ}$ C; 56 days; 93 $\pm$ 2/–3% RH	$\pm$ (0,05% + 0,01 Ω)	$\pm$ (0,1% + 0,01 Ω)	$\pm$ (0,25% + 0,05 Ω)
4.23		climatic sequence:				
4.23.2	2 (Ba)	dry heat	125 $^{\circ}$ C; 16 h			
4.23.3	30 (Db)	damp heat, cyclic	55 $^{\circ}$ C; 24 h; 90 to 100% RH; 1 cycle			
4.23.4	1 (Aa)	cold	–55 $^{\circ}$ C; 2 h			
4.23.5	13 (M)	low air pressure	8,5 kPa; 2 h; 15 to 35 $^{\circ}$ C			
4.23.6	30 (Db)	damp heat, cyclic	55 $^{\circ}$ C; 5 days; 95 to 100% RH; 5 cycles	$\pm$ (0,05% + 0,01 Ω) no visible damage	$\pm$ (0,1% + 0,01 Ω) no visible damage	$\pm$ (0,25% + 0,05 Ω) no visible damage
4.13	–	short time overload	room temperature; $U = 2,5 \times \sqrt{P_{70}} \times R$ or $U = 2 \times U_{max}$; 5 s	$\pm$ (0,01% + 0,01 Ω) no visible damage	$\pm$ (0,02% + 0,01 Ω) no visible damage	$\pm$ (0,05% + 0,01 Ω) no visible damage
4.19	14 (Na)	rapid change of temperature	30 minutes at LCT and 30 minutes at UCT; 5 cycles	$\pm$ (0,01% + 0,01 Ω) no visible damage	$\pm$ (0,02% + 0,01 Ω) no visible damage	$\pm$ (0,05% + 0,01 Ω) no visible damage
4.29	45 (XA)	component solvent resistance	isopropyl alcohol +23 $^{\circ}$ C; toothbrush method	marking legible; no visible damage		
4.18.2	20 (Tb)	resistance to soldering heat	unmounted components; 260 $\pm$ 5 $^{\circ}$ C; 10 $\pm$ 1 s	$\pm$ (0,01% + 0,01 Ω) no visible damage	$\pm$ (0,02% + 0,01 Ω) no visible damage	$\pm$ (0,05% + 0,01 Ω) no visible damage
4.17	20 (Ta)	solderability	+235 $^{\circ}$ C; 2 s solder bath method	good tinning ($\geq$ 95 covered); no visible damage		
4.22	6 (B4)	vibration	6 h; 10 to 2000 Hz 1,5 mm or 196 m/s ²	$\pm$ (0,01% + 0,01 Ω)	$\pm$ (0,02% + 0,01 Ω)	$\pm$ (0,05% + 0,01 Ω)

Precision leaded resistors

**MBA 0204; MBB 0207;
MBE 0414**

IEC 60115-1 CLAUSE	IEC 60068-2 TEST METHOD	TEST	PROCEDURE	REQUIREMENTS PERMISSIBLE CHANGE ($\Delta R/R$)		
				STABILITY CLASS 0,05	STABILITY CLASS 0,1	STABILITY CLASS 0,25
			stability for product types:			
			MBA 0204	100 Ω to 100 k Ω	43 Ω to <100 Ω ; >100 k Ω to 221 k Ω	22 Ω to <43 Ω ; >221 k Ω to 332 k Ω
			MBB 0207	100 Ω to 270 k Ω	43 Ω to <100 Ω ; >270 k Ω to 510 k Ω	10 Ω to <43 Ω ; > 510 k Ω to 1 M Ω
			MBE 0414	100 Ω to 470 k Ω	43 Ω to <100 Ω ; >470 k Ω to 1 M Ω	22 Ω to <43 Ω ; >1 M Ω to 1,5 M Ω
4.16	21 (U _{a1}) 21 (U _b) 21 (U _c)	robustness of terminations	tensile, bending and torsion	$\pm(0,01\% + 0,01 \Omega)$	$\pm(0,02\% + 0,01 \Omega)$	$\pm(0,05\% + 0,01 \Omega)$
4.7	–	voltage proof	$U_{rms} = 100 \text{ V}; 60 \text{ s}$	no flashover or breakdown		

Notes

1. $\pm(0,03\% + 0,01 \Omega)$ for MBB 0207.
2. $\pm(0,15\% + 0,05 \Omega)$ for MBB 0207.