
















Specification

Global Part Number	DEBB33D102KA2B
Previous Part Number	DE0805B102K2K
Body Dia. D	8mm max.
Lead Spacing F	5.0mm ?1.0mm
Body Thickness T	5.0mm max.
Lead Dia. phi-d	0.6mm ?0.05mm
Coating Extension e	Up to the end of crimp
TC Code	B
Capacitance Change (1)	?10%
Capacitance Change (2)	
Temp. Range for TC	-25 to +85deg.
Operating Temp. Range	-25 to +85deg.
Capacitance	1000pF ?10%
Rated Voltage	2000Vdc
Packaging Form	Bulk

Minimum Quantity

180mm Paper Tape	
180mm Embossed Tape	
330mm Paper Tape	
330mm Embossed Tape	
Bulk Case	
Bulk(Bag)	1000
Ammo Pack	
320Reel	
Magazine	
Box	

Details

-  [Part Numbering](#)
-  [Appearance](#)
-  [Dimensions](#)
-  [Features and Application](#)
-  [Spec. and Test Methods](#)
-  [Packaging](#)
-  [Caution \(storage and operating condition\)](#)
-  [Caution \(rating\)](#)
-  [Caution \(soldering and mounting\)](#)
-  [Caution \(handling\)](#)
-  [Notice \(soldering and mounting\)](#)
-  [Cap.-Temp.Char.](#)
-  [Cap.-DC Bias Char.](#)
-  [Notice \(rating\)](#)
-  [Marking](#)

Product specifications in this catalog are as of May 2006,
 and are subject to change or obsolescence without notice.
 Please approve our product specifications or transact the approval sheet before ordering.
 Please read rating and !Cautions first.

All products and company names herein are trademarks or registered trademarks of their respective owners.

UP ^