

1.8 WATT REGULATED DC/DC CONVERTER

PWR60XX



FEATURES

- Low Cost
- Low Noise
- Industry-Standard Package
- Single and Dual Outputs
- High Isolation Voltage Option Available
- Linear Output Regulation
- Internal Input and Output Filtering
- Low EMI Transformer Design
- No External Components Required
- Thermal Shutdown Protection


DESCRIPTION

The PWR60XX Series offers a low-cost alternative for some of the most popular DC/DC converters industry wide. Each model has very low noise and an outstanding MTTF. The superior reliability, excellent filtering, and low cost make it an excellent choice for industry-standard usage.

The series includes eleven models (other input and output voltages are available upon request), all set in an encapsulant for excellent thermal dissipation for internal components. The use of surface-mount devices and manufacturing processes combined with the encapsulation process, provides the user a product that is more environmentally rugged.

The PWR60XX has full isolation between input and output to give the designer maximum flexibility in grounding options and polarity configurations. The outputs are protected against shorts to increase the units survivability in harsh environments.

MECHANICAL



Internet: <http://www.cdpowerelectronics.com>

Power Electronics Division, United States
3400 E Britannia Drive, Tucson, Arizona 85706
Phone: 800.547.2537 Fax: 520.770.9369

Power Electronics Division, Europe
C&D Technologies (Power Electronics) Ltd.
132 Shannon Industrial Estate, Shannon, Co. Clare, Ireland
Tel: +353.61.474.133 Fax: +353.61.474.141

ELECTRICAL SPECIFICATIONS

Specifications typical at $T_A = +25^{\circ}\text{C}$, rated input voltage, rated output current unless otherwise specified.

MODEL	NOMINAL INPUT VOLTAGE (V _{DC})	RATED OUTPUT VOLTAGE (V _{DC})	RATED OUTPUT CURRENT (mA)	INPUT CURRENT		REFLECTED RIPPLE CURRENT (mAp-p)	EFFICIENCY (%)
				NO LOAD (mA)	RATED LOAD (mA)		
PWR6000	5	5	360	70	655	15	55
PWR6004	5	±12	±75	70	570	15	63
PWR6005	5	±15	±60	70	555	15	65
PWR6006	12	5	360	30	275	10	55
PWR6010	12	±12	±75	30	240	10	63
PWR6011	12	±15	±60	30	230	10	65
PWR6012	15	5	360	25	220	8	55
PWR6016	15	±12	±75	25	190	8	63
PWR6017	15	±15	±60	25	185	8	65
PWR6018	24	5	360	13	120	12	62
PWR6023	24	±15	±60	13	120	12	62

NOTE: Other input to output voltages may be available. Please consult factory.

COMMON SPECIFICATIONS


Specifications typical at $T_A = +25^{\circ}\text{C}$, rated input voltage, rated output current unless otherwise specified.

PARAMETER	CONDITIONS	MIN	TYP	MAX	UNITS
INPUT	PWR6000	4.65	5.0	5.5	V _{DC}
	PWR6004	4.65	5.0	5.5	V _{DC}
	PWR6005	4.65	5.0	5.5	V _{DC}
	PWR6006	10.9	12.0	13.2	V _{DC}
	PWR6010	10.9	12.0	13.2	V _{DC}
	PWR6011	10.9	12.0	13.2	V _{DC}
	PWR6012	13.9	15.0	16.5	V _{DC}
	PWR6016	13.9	15.0	16.5	V _{DC}
	PWR6017	13.9	15.0	16.5	V _{DC}
	PWR6018	21.6	24	26.4	V _{DC}
	PWR6023	21.6	24	26.4	V _{DC}
ISOLATION (Standard)					
Rated Voltage		500			V _{DC}
Test Voltage		500			V _{pk}
Resistance			10		GΩ
Capacitance			27		pF
Leakage Current	V _{ISO} = 240V _{AC} , 60Hz			5	μArms
ISOLATION (–HV Option)					
Rated Voltage		1000			V _{DC}
Test Voltage		3000			V _{pk}
Resistance			10		GΩ
Capacitance			27		pF
Leakage Current	V _{ISO} = 240V _{AC} , 60Hz			5	μArms
OUTPUT					
Rated Power	–25°C - T _A - +70°C		1.8		Watts
Voltage Setpoint Accuracy	Rated Load, Nominal Vin			±2	%
Temperature Coefficient			±0.01		%/°C
Ripple and Noise	BW = DC to 10MHz		20	45	mVp-p
REGULATION					
Line	High Line to Low Line		±0.2	±1.0	%
Load	Full Load to No Load		0.5	1.0	%
GENERAL					
Switching Frequency			150		kHz
Package Weight			20		g
MTTF per MIL-HDBK-217, RevE	Circuit Stress Method		930,000		Hr
TEMPERATURE					
Specification		–25	+25	+70	°C
Operation		–25		+100	°C
Storage		–40		+110	°C


ABSOLUTE MAXIMUM RATINGS

Output Short-Circuit Duration
 Outputs to Common Continuous
 Output to Output Momentary
 Output Power 2.0W
 Lead Temperature +300°C
 (soldering, 10 seconds max)

TYPICAL APPLICATIONS












ORDERING INFORMATION



TYPICAL PERFORMANCE CURVES

$T_A = +25^\circ\text{C}$, Rated Input Voltage, Rated Output Current unless otherwise noted.



TYPICAL PERFORMANCE CURVES

$T_A = +25^\circ\text{C}$, Rated Input Voltage, Rated Output Current unless otherwise noted.

