



MagLev Motor Fan

19.3~27 CFM




Model	P/N	Bearing ● VAPO ⊙ 2BALL	Rating Voltage (VDC)	Power Current (AMP)	Power Consumption (WATTS)	Speed (RPM)	Air Flow (CFM)	Static Pressure (Inch-H ₂ O)	Noise (dBA)	Weight (g)
KDE1206PTVX	MS.A.GN	●	12	0.23	2.8	5200	27.0	0.31	36.5	55
KDE1206PTV1	MS.A.GN	●	12	0.14	1.7	4500	23.5	0.21	33.5	55
KDE1206PTV2	MS.A.GN	●	12	0.07	0.8	3800	19.3	0.15	29.0	55
KDE2406PTVX	MS.A.GN	●	24	0.12	2.9	5200	27.0	0.31	36.5	56
KDE2406PTV1	MS.A.GN	●	24	0.08	1.9	4500	23.5	0.21	33.5	56
KDE2406PTV2	MS.A.GN	●	24	0.05	1.2	3800	19.3	0.15	29.0	56

*High air flow products please see page 41.



(Units : mm)



*All model could be customized on voltage or any other requirements to fit your need.

*Specifications subject to change without notice. Please Visit SUNON web site at <http://www.sunon.com> for update information.