

# DATA SHEET

## GENERAL PURPOSE CHIP RESISTORS

RC1218 (Pb Free)  
5%, 1%



## SCOPE

This specification describes RC1218 series chip resistors with lead-free terminations made by thick film process.

## ORDERING INFORMATION

Part number is identified by the series, size, tolerance, packing type, temperature coefficient, taping reel and resistance value.

### PHYCOMP ORDERING CODE

#### I2NC CODE

	<b>2322</b>	<b>XXX</b>	<b>XXXXX</b>	<b>L</b>	
	(1)	(2)	(3)	(4)	
TYPE/ 1218	START IN <sup>(1)</sup>	TOL. (%)	RESISTANCE RANGE	EMBOSSED TAPE ON REEL (units) <sup>(2)</sup>	
				4,000	
PRC20I	2322	±5%	1 to 1 MΩ	735 64xxx	
PRC20I	2322	±1%	1 to 1 MΩ	735 7xxxx	
Jumper	2322	-	0 Ω	735 90007	

(1) The resistors have a 12-digit ordering code starting with 2322.

(2) The subsequent 4 or 5 digits indicate the resistor tolerance and packaging.

(3) The remaining 4 or 3 digits represent the resistance value with the last digit indicating the multiplier as shown in the table of "Last digit of I2NC".

(4) "L" means lead-free terminations.

┐ Last digit of I2NC

Resistance decade <sup>(3)</sup>	Last digit
0.01 to 0.0976 Ω	0
0.1 to 0.976 Ω	7
1 to 9.76 Ω	8
10 to 97.6 Ω	9
100 to 976 Ω	1
1 to 9.76 kΩ	2
10 to 97.6 kΩ	3
100 to 976 kΩ	4
1 to 9.76 MΩ	5
10 to 97.6 MΩ	6

#### ORDERING EXAMPLE

The ordering code of a PRC20I resistor, value 56 Ω with ±1% tolerance, supplied in tape of 4,000 units per reel is:  
232273575609L.

Example:	0.02 Ω	=	0200 or 200
	0.3 Ω	=	3007 or 307
	1 Ω	=	1008 or 108
	33 kΩ	=	3303 or 333
	10 MΩ	=	1006 or 106

#### CTC CODE

<b>RC1218</b>	<b>X</b>	<b>X</b>	<b>X</b>	<b>XX</b>	<b>XXXX</b>	<b>L</b>
(1)	(2)	(3)	(4)	(5)	(6)	

#### (1) TOLERANCE

F = ±1%

J = ±5%

#### (2) PACKAGING TYPE

K = Embossed taping reel

#### (3) TEMPERATURE COEFFICIENT OF RESISTANCE

- = Base on spec

#### (4) TAPING REEL

07 = 7 inch dia. Reel

#### (5) RESISTANCE VALUE

5R6, 56R, 560R, 5K6, 56K, 22M

#### (6) RESISTOR TERMINATIONS

L = Lead free terminations (pure Tin)

#### ORDERING EXAMPLE

The ordering code of a RC1218 chip resistor, value 56 Ω with ±1% tolerance, supplied in 7-inch tape reel is: RC1218FK-0756RL.

## NOTE

1. The "L" at the end of the code is only for ordering. On the reel label, the standard CTC or I2NC will be mentioned an additional stamp "LFP"= lead free production.
2. Products with lead in terminations fulfil the same requirements as mentioned in this datasheet.
3. Products with lead in terminations will be phased out in the coming months (before July 1st, 2006)

## MARKING

### RC1218




Fig. 1 Value=100  $\Omega$

E-24 series: 3 digits

First two digits for significant figure and 3rd digit for number of zeros




Fig. 2 Value=10 K $\Omega$

Both E-24 and E-96 series: 4 digits

First three digits for significant figure and 4th digit for number of zeros

For marking codes, please see EIA-marking code rules in data sheet “Chip resistors instruction”.

## CONSTRUCTION

The resistors are constructed out of a high-grade ceramic body. Internal metal electrodes are added at each end and connected by a resistive paste. The composition of the paste is adjusted to give the approximate required resistance and laser cutting of this resistive layer that achieves tolerance trims the value. The resistive layer is covered with a protective coat and printed with the resistance value. Finally, the two external terminations (pure Tin) are added. See fig. 3.




Fig. 3 Chip resistor construction

## DIMENSIONS

Table I

TYPE	RC1218
L (mm)	3.10 $\pm$ 0.10
W (mm)	4.60 $\pm$ 0.10
H (mm)	0.55 $\pm$ 0.10
$l_1$ (mm)	0.45 $\pm$ 0.20
$l_2$ (mm)	0.40 $\pm$ 0.20

For dimension see Table I




Fig. 4 Chip resistor dimension

ELECTRICAL CHARACTERISTICS

Table 2

CHARACTERISTICS	RC1218 1 W	
Operating Temperature Range	-55 °C to +155 °C	
Maximum Working Voltage	200 V	
Maximum Overload Voltage	500 V	
Dielectric Withstanding Voltage	500 V	
Resistance Range	5% (E24)	1 $\Omega$ to 1 M $\Omega$
	1% (E96)	1 $\Omega$ to 1 M $\Omega$
	Zero Ohm Jumper < 0.02 $\Omega$	
Temperature Coefficient	10 $\Omega$ < R $\leq$ 1 M $\Omega$	$\pm 100$ ppm/°C
	1 $\Omega$ < R $\leq$ 10 $\Omega$	$\pm 200$ ppm/°C
Jumper Criteria	Rated Current	6.0 A
	Maximum Current	10.0 A

FOOTPRINT AND SOLDERING PROFILES

For recommended footprint and soldering profiles, please see the special data sheet “Chip resistors mounting”.

ENVIRONMENTAL DATA

For material declaration information (IMDS-data) of the products, please see the separated info “Environmental data”.

PACKING STYLE AND PACKAGING QUANTITY

Table 3 Packing style and packaging quantity

PRODUCT TYPE	PACKING STYLE	REEL DIMENSION	QUANTITY PER REEL
RC1218	Embossed taping reel (K)	7" (178 mm)	4,000 units

**NOTE**

1. For embossed tape and reel specification/dimensions, please see the special data sheet “Packing” document.

## FUNCTIONAL DESCRIPTION

### POWER RATING

RC1218 rated power at 70°C is 1 W

### RATED VOLTAGE

The DC or AC (rms) continuous working voltage corresponding to the rated power is determined by the following formula:

$$V = \sqrt{P \times R}$$

Where

V=Continuous rated DC or  
AC (rms) working voltage (V)

P=Rated power (W)

R=Resistance value ( $\Omega$ )

### PULSE LOADING CAPABILITIES




Fig. 5 Maximum dissipation ( $P_{max}$ ) in percentage of rated power as a function of the operating ambient temperature ( $T_{amb}$ )




Fig. 6 Maximum permissible peak pulse voltage without failing to open circuit' in accordance with DIN IEC 60040 (CO) 533 for type: RC1218




Fig. 7 Pulse on a regular basis for type: RC1218; maximum permissible peak pulse power as a function of pulse duration for single pulse and repetitive pulse  $t_p/t_i = 1000$




Fig. 8 Pulse on a regular basis for type: RC1218; maximum permissible peak pulse voltage as a function of pulse duration

## TESTS AND REQUIREMENTS

Table 4 Test condition, procedure and requirements

TEST	TEST METHOD	PROCEDURE	REQUIREMENTS				
Temperature Coefficient of Resistance (T.C.R.)	MIL-STD-202F-method 304; JIS C 5202-4.8	At +25/−55 °C and +25/+125 °C  Formula:  $T.C.R = \frac{R_2 - R_1}{R_1 (t_2 - t_1)} \times 10^6 \text{ (ppm/°C)}$  Where t <sub>1</sub> =+25 °C or specified room temperature t <sub>2</sub> =−55 °C or +125 °C test temperature R <sub>1</sub> =resistance at reference temperature in ohms R <sub>2</sub> =resistance at test temperature in ohms	Refer to table 3				
Thermal Shock	MIL-STD-202F-method 107G; IEC 60115-1 4.19	At −65 (+0/−10) °C for 2 minutes and at +155 (+10/−0) °C for 2 minutes; 25 cycles	±(0.5%+0.05 Ω) for 1% tol. ±(1.0%+0.05 Ω) for 5% tol.				
Low Temperature Operation	MIL-R-55342D-Para 4.7.4	At −65 (+0/−5) °C for 1 hour; RCWV applied for 45 (+5/−0) minutes	±(0.5%+0.05 Ω) for 1% tol . ±(1.0%+0.05 Ω) for 5% tol. No visible damage				
Short Time Overload	MIL-R-55342D-Para 4.7.5; IEC 60115-1 4.13	2.5 × RCWV applied for 5 seconds at room temperature	±(1.0%+0.05 Ω) for 1% tol. ±(2.0%+0.05 Ω) for 5% tol. No visible damage				
Insulation Resistance	MIL-STD-202F-method 302; IEC 60115-1 4.6.1.1	RCOV for 1 minute <table><tr><td>Type</td><td>RC1218</td></tr><tr><td>Voltage (DC)</td><td>500 V</td></tr></table>	Type	RC1218	Voltage (DC)	500 V	≥10 GΩ
Type	RC1218						
Voltage (DC)	500 V						
Dielectric Withstand Voltage	MIL-STD-202F-method 301; IEC 60115-1 4.6.1.1	Maximun voltage (V <sub>rms</sub> ) applied for 1 minute <table><tr><td>Type</td><td>RC1218</td></tr><tr><td>Voltage (AC)</td><td>500 V<sub>rms</sub></td></tr></table>	Type	RC1218	Voltage (AC)	500 V <sub>rms</sub>	No breakdown or flashover
Type	RC1218						
Voltage (AC)	500 V <sub>rms</sub>						
Resistance to Soldering Heat	MIL-STD-202F-method 210C; IEC 60115-1 4.18	Unmounted chips; 260 ±5 °C for 10 ±1 seconds	±(0.5%+0.05 Ω) for 1% tol. ±(1.0%+0.05 Ω) for 5% tol. No visible damage				
Life	MIL-STD-202F-method 108A; IEC 60115-1 4.25.1	At 70±2 °C for 1,000 hours; RCWV applied for 1.5 hours on and 0.5 hour off	±(1%+0.05 Ω) for 1% tol. ±(3%+0.05 Ω) for 5% tol.				

TEST	TEST METHOD	PROCEDURE	REQUIREMENTS	
Solderability	MIL-STD-202F-method 208A;	Solder bath at $245 \pm 3$ °C	Well tinned ( $\geq 95\%$ covered)	
	IEC 60115-1 4.17	Dipping time: $2 \pm 0.5$ seconds	No visible damage	
Bending Strength	JIS C 5202.6.14;	Resistors mounted on a 90 mm glass epoxy resin PCB (FR4) Bending: 2 mm	$\pm(1.0\%+0.05 \Omega)$ for 1% tol.	
	IEC 60115-1 4.15		$\pm(1.0\%+0.05 \Omega)$ for 5% tol. No visible damage	
Resistance to Solvent	MIL-STD-202F-method 215; IEC 60115-1 4.29	Isopropylalcohol ( $C_3H_7OH$ ) or dichloromethane ( $CH_2Cl_2$ ) followed by brushing	No smeared	
Noise	JIS C 5202 5.9; IEC 60115-1 4.12	Maximum voltage ( $V_{rms}$ ) applied.	<b>Resistors range</b>	<b>Value</b>
			$R < 100 \Omega$	10 dB
			$100 \Omega \leq R < 1 K\Omega$	24 dB
			$1 K\Omega \leq R < 10 K\Omega$	34 dB
			$10 K\Omega \leq R < 100 K\Omega$	44 dB
			$100 K\Omega \leq R < 1 M\Omega$	46 dB
			$1 M\Omega \leq R \leq 22 M\Omega$	48 dB
Humidity (steady state)	JIS C 5202 7.5; IEC 60115-8 4.24.8	1,000 hours; $40 \pm 2$ °C; $93(+2/-3)\%$ RH RCWV applied for 1.5 hours on and 0.5 hour off	$\pm(0.5\%+0.05 \Omega)$ for 1% tol. $\pm(2.0\%+0.05 \Omega)$ for 5% tol.	
Leaching	EIA/IS 4.13B; IEC 60115-8 4.18	Solder bath at $260 \pm 5$ °C Dipping time: $30 \pm 1$ seconds	No visible damage	
Intermittent Overload	JIS C 5202 5.8	At room temperature; $2.5 \times$ RCWV applied for 1 second on and 25 seconds off; total 10,000 cycles	$\pm(1.0\%+0.05 \Omega)$ for 1% tol. $\pm(2.0\%+0.05 \Omega)$ for 5% tol.	
Resistance to Vibration	On request	On request		
Moisture Resistance Heat	MIL-STD-202F-method 106F; IEC 60115-1 4.24.2	42 cycles; total 1,000 hours Shown as figure 9	$\pm(0.5\%+0.05\Omega)$ for 1% tol. $\pm(2.0\%+0.05\Omega)$ for 5% tol. No visible damage	






Fig. 9 Moisture resistance test requirements

REVISION HISTORYREVISION DATE CHANGE NOTIFICATION DESCRIPTION

Version I	Oct 13, 2004	-	<ul style="list-style-type: none"><li>- New datasheet for 1218 thick film 1% and 5% with lead-free terminations</li><li>- Replace the 1218 part of pdf files: PRC201_51_17</li><li>- Test method and procedure updated</li><li>- Taping reel changed from 11" to 7" and quantity per reel from 5K to 4K as well</li></ul>
-----------	--------------	---	---