

Fuse Clips For Printed Circuit Boards

219083 *

For 1/4" Dia. Fuses (With End Stops & Without End Stops)

Catalog Number	Clip Mat.*	Finish	
1A1907-06	Spg Br	Bright Tin	
1A1907-05	BeCu*	Silver	
1A1907-03	BeCu*	Bright Tin	
1A3398-07†	Spg Br	Bright Tin	
1A1119-10	Spg Br	Bright Tin	
1A1119-05	BeCu*	Silver	
1A1119-04	BeCu*	Bright Tin	

For 1/4" Dia. Fuses (Without End Stops)

Catalog Number	Clip Mat.*	Finish	
1A1120-09	Spg Br	Bright Tin	
1A1120-05	BeCu*	Silver	
1A1120-06	BeCu*	Bright Tin	

For 1/4" Dia. Fuses (With and Without End Stops)

Catalog Number	Clip Mat.*	Finish	
1A4533-01	Be Cu*	Bright Tin	
1A4533-06	Spg Br	Bright Tin	
1A4534-01	BeCu*	Bright Tin	
1A4534-06	Spg Br	Bright Tin	

*Beryllium copper recommended for currents higher than 15 amps (1/4" clips); 10 amps (5mm clips). Spg Br—Spring Bronze; BeCu—Beryllium Copper.

For 5mm Dia. (With End Stops)


Catalog Number	Clip Mat.*	Finish	
1A3399-10	Spg Br	Bright Tin	
1A3399-01	BeCu*	Silver	
1A3399-04	BeCu*	Bright Tin	
High Profile			
1A5018-10	Spg Br	Bright Tin	
1A5018-7		Silver	

For 13/32" Dia. Fuses (20 Amps Max.)

Catalog Number	Clip Mat.*	Finish	
1A3400-09	Spg Br	Bright Tin	

*Beryllium copper recommended for currents higher than 15 amps (1/4" clips); 10 amps (5mm clips). Spg Br—Spring Bronze; BeCu—Beryllium Copper.

Footprint Dimensions



Fuse Clip Catalog Number

Dim.	Fuse Size	1A1907-	1A1119-	1A1120-	1A3399-	1A3400-	1A4533-	1A4534-	1A5018-
A	7/8" (22.2mm)	1.00" (25.40mm)	1.00" (25.40mm)	1.00" (25.40mm)	—	—	1.00" (25.40mm)	1.00" (25.40mm)	—
	1" (25.4mm)	1.125" (28.58mm)	1.125" (28.58mm)	1.125" (28.58mm)	—	—	1.125" (28.58mm)	1.125" (28.58mm)	—
	1 1/4" (31.8mm)	1.375" (34.92mm)	1.375" (34.92mm)	1.375" (34.92mm)	—	—	1.375" (34.92mm)	1.375" (34.92mm)	—
	1 5/8" (34.93mm)	—	—	—	—	1.50" (38.10mm)	—	—	—
	1 3/2" (38.10mm)	—	—	—	—	1.625" (41.28mm)	—	—	—
	20mm	—	—	—	.875" (22.23mm)	—	—	—	.820" ± .015" (20.80 ± .38mm)
B Tabs		.295"–.305" (7.49–7.75mm)	.295"–.305" (7.49–7.75mm)	.295"–.305" (7.49–7.75mm)	.200" (5.08mm)	.405" (10.29mm)	.300" (7.62mm)	.300" (7.62mm)	.180" (4.6mm)
C (4 holes)		.067"–.070" (1.70–1.78mm)	.093" ± .002" (2.36 ± .05mm)	.093" ± .002" (2.36 ± .05mm)	.067"–.070" (1.70–1.78mm)	.091"–.095" (2.31–2.41mm)	.067"–.070" (1.70–1.78mm)	.067"–.070" (1.70–1.78mm)	.053" ± .002" (1.35 ± .05mm)
Board Thickness		.093" (2.36mm)	.062" to .125" (1.57 to 3.18mm)	.062" to .125" (1.57 to 3.18mm)	.093" (2.36mm)	.125" (3.18mm)	.062" (1.57mm)	.062" (1.57mm)	.093" (2.36mm)