# SMT Power Inductors–DO3308 Series



With a height of only .118" (3,0 mm), Coilcraft's new DO3308 Series of surface mount power inductors is ideal for PDA, palmtop and other handheld applications.

Available in 13 versions with inductance ratings from 10 to 1000 µH, these parts will handle currents up to 2 Amps. They have a  $.370 \times .510 (9.4 \times 13.0)$  base and a flat top for reliable pick and place handling.

In addition to the standard versions shown here, custom inductors are available to meet your exact requirements.

Coilcraft Designer's Kit C109 contains three samples each of the standard parts shown. To order, contact Coilcraft or visit http://order.coilcraft.com.

#### **PSpice models** SEE CATALOG, WEB SITE OR CD


| Part<br>Num-ber   | $\begin{array}{c} \text{L} \pm 20\%^1 \\ \text{($\mu$H)} \end{array}$ | DCR max. (Ω)                    | SRF typ<br>(MHz)           | Isat²<br>(A)                    | Irms³<br>(A)             |
|---|---|---------------------------------|----------------------------|---------------------------------|--------------------------|
| DO3308P-103<br>DO3308P-153<br>DO3308P-223<br>DO3308P-333<br>DO3308P-473 | 10<br>15<br>22<br>33<br>47  | .11<br>.15<br>.23<br>.30        | 35<br>33<br>25<br>19<br>14 | 2.4<br>2.0<br>1.6<br>1.4<br>1.0 | 2.0<br>1.5<br>1.3<br>1.1 |
| DO3308P-683<br>DO3308P-104<br>DO3308P-154<br>DO3308P-224<br>DO3308P-334 | 68<br>100<br>150<br>220<br>330  | .66<br>.84<br>1.2<br>1.9<br>2.7 | 12<br>10<br>8<br>6<br>5    | .9<br>.7<br>.6<br>.5            | .7<br>.6<br>.5<br>.4     |
| DO3308P-474<br>DO3308P-684<br>DO3308P-105                               | 470<br>680<br>1000  | 4.0<br>5.3<br>8.4               | 4<br>3<br>2.5              | .3<br>.2<br>.1                  | .2<br>.1<br>.05          |

For environmental data see Product Specifications section.

1. Inductance tested at 100 kHz, .1 Vrms

2. Inductance drop = 10% typ. at rated Isat.


- ΔT = 30° C rise typ. at Irms.
  Operating temperature range –40
  Electrical specifications at 25° C. -40° C to +85° C



Parts/reel: 13" 1000 Tape width: 24 mm For packaging data see Tape and Reel Specifications section.

# SMT Power Inductors—DO3308 Series

### Typical L vs Frequency



## Typical L vs Current

