

Position position — 32
6x 10,16 (=60,96)
10,16 3,81
 $\phi 2,8 \pm 0,1$
alle Löcher all holes
 $\oplus \phi 0,05$ 1,6 ± 0,1 1,27 10,16
7x 10,16 (=71,12)
88,9 ± 0,1

X Lochbild board drillings

d z Reihe row

W 10:1
Querschnitt der Lötanschlüsse:
cross-section of solder terminations:

0,8 ± 0,025 1,16 ± 0,02
0,93mm²

2:1
Montageloch-Mittellinie mounting hole center-line
Kontakt-Typ pin-type — A B C
Referenzebene Tiefe datum plane depth
Standard/standard 6,25 ± 0,2 Voreiler/preleading 1,5 7,75 ± 0,2 Standard/standard 6,25 ± 0,2
5,08 5,08 8,35 ± 0,05 5,35 ± 0,05 6,5 12,75 ± 0,05

X Kontaktbelegung contact loading

32 30 28 26 24 22 20 18 16 14 12 10 8 6 4
C C C C C C C C
B A A A A A A A
d z

Z
position 32 10,16 1,27 Reihe/row z position 4
10,16 3,81 Reihe/row d position 8
6x 10,16 (=60,96)

Sollbruchstelle für Kodierung breaking point for coding
Z
88,9 ± 0,1
2,58 ± 0,03
X
93,95 ± 0,05

Y
W
3,87 ± 0,03
6 ± 0,1

Kontaktoberfläche Ag contact plating Ag

All Dimensions in mm Original Size DIN A 3		Techn. Character.		Nicht tolerierte Maß / Free size tolerances IEC 60603-2	
		IEC 60603-2			
		Dat.	Name	Maßstab/Scale	
		Detail.	13.10.04 Leh.	1:1	
		Insp.	13.10.04 kfoe	2:1 10:1	
		Stand.			
32352		HARTING Electronics GmbH & Co. KG D-32339 ESPELKAMP		HARTING	
Mod.	Dat.	Name			

Bauform/type H 15
Messerleiste Einlötl gewinkelt male connector solder angled
TB 09 06 115 2932 Blatt/page Sub.

 All Dimensions in mm Original Size DIN A 3			Techn. Character. IEC 60603-2			Nicht tolerierte Maß/Free size tolerances IEC 60603-2						
				Dat.	Name	Maßstab/Scale 1 : 1 2 : 1 10 : 1			Bauform/type H 15 Messerleiste Einlöt gewinkelt <i>male connector solder angled</i>			
			Detail.	13.10.04	Leh.							
			Insp.	13.10.04	kfoe							
			Stand.									
			HARTING Electronics GmbH & Co. KG						TB 09 06 115 2932			Blatt/ page /
32352			D-32339 ESPELKAMP									
Mod.	Dat.	Name										