



Part: 0452001.
Series: 452 Series - NANO²® Slo-Blo® Subminiature Surface Mount Fuse
Technology: Surface Mount (SMT)

PARAMETERS		
Package Type	Pkg Type	Subminiature Ceramic
Mount Method	Mount	Surface Mount
Peak Pulse Current - 10x1000Âµs	I _{PP} 10x1000Âµs (A)	0
Peak Pulse Current - 10x160Âµs	I _{PP} 10x160Âµs (A)	0
Peak Pulse Current - 10x560Âµs	I _{PP} 10x560Âµs (A)	0
Peak Pulse Current - 2x10Âµs	I _{PP} 2x10Âµs (A)	0
	Mount2-NA	Fuse Block/ Clip / Holder
Fuse Opening Characteristic	Opening	Slo-Blo®
Lead-Free	Pb Free	Y
Package Size / Form Factor	Size	Subminiature
Current Rating	Amp Rating (A)	1.0000
Voltage Rating	Voltage Rating (V)	125
Nominal Cold Resistance	Resistance (Ohms)	0.2250
Norminal Melting I ² t	I ² t (A ² Sec)	1.9800
Certifications	Cert	 Interrupt Ratings 50A @ 125V 50A @ 125V



PROTECTS AGAINST:

Other Threats

Short Circuit/Current Overload