

Catalog

- ▶ [Home](#)
- ▶ [Part Number Search](#)
- ▶ [Document Search](#)
- ▶ [CAD Model Search](#)
- ▶ [Text Search](#)
- ▶ [Alternate/Lead Free Part Search](#)
- ▶ [Multiple Part Comparison](#)
- ▶ [Alphabetical Search](#)
- ▶ [Brand Search](#)
- ▶ [Industry Product Search](#)
- ▶ [Product Type Search](#)
- ▶ [Product Family Search](#)
- ▶ [Competitor Cross Reference](#)
- ▶ [Lead Free Solutions](#)
- ▶ [Tool Search](#)
- ▶ [Help/Glossary](#)

Relays**➡ Industrial Relays (General Purpose)****SCHRACK** RY612024  [Active](#)**Directive 2002/95/EC
Compliant**[RoHS Compliant](#)**(Tyco Electronics P/N: 2-1393225-9)**[Search for Parts](#)

Product Documentation - Please use the customer drawing for all design activity.	
Customer Drawing	Drawings & Specifications
No Customer Drawings available at this time.	No Documents available at this time.

Related Part Information		
General Information	eCommerce	Related Part Information
<ul style="list-style-type: none"> ▶ General Info ▶ Sales Info 	<ul style="list-style-type: none"> ▶ Pricing ▶ Product Availability 	<ul style="list-style-type: none"> ▶ Tooling

Photos & Line Drawings - The photographs and/or line drawings are representative images of a product for viewing purposes only.

[Product Photo](#)**Searchable Features:****Other Properties:**

Brand:	Schrack
RoHS/ELV Compliance:	RoHS compliant, ELV compliant
Lead Free Solder Process:	Wave solder capable to 240° C
Series:	RYII
Contact Arrangement:	1 Form C, SPDT, 1 C/O
Contact Current Rating (Amps.):	8
Coil Magnetic System:	Monostable
Coil Suppression Diode:	Without
Coil Selection Criteria:	Nominal Voltage
Coil Resistance (Ω):	2350
Coil Power, Nominal (mW):	220

RoHS/ELV Compliance History:	Altered to comply with RoHS directive
Approx. Dimensions (L x W x H) (mm [in]):	28.50 x 10.10 x 12.30 [1.122 x .398 x .484]
Polarized:	No
Wiring Diagram:	1 Form C
Approved Standards:	UL Recognized, SEV Approved, Semko Approved, OVE, CSA Certified, VDE Component Mark
Comment:	Pinning 3.2 mm

Actuating System:	DC
Coil Latching:	No
Mounting Options:	PC Board, Socket
Termination Type:	Printed Circuit Terminals
Input Voltage (VDC):	24
Enclosure:	Washable
Relay Type:	PCB, Power
LED Indicator:	Without
Contact Material:	Silver Nickel, Gold Plated

[Copyright](#) and [Privacy Statement](#)

Visit [Tyco International, Ltd.](#)

[Products](#) | [Catalog](#) | [Brands](#) | [Industries](#) | [Commerce](#) | [Supplier](#) | [Contact Us](#) | [About](#) | [Home](#)

