

DH

S20X-0100-XXX

1.27mm x 1.27mm

BOXED TYPE

DUAL ROW

SMT TYPE

WITH POST

SINGLE ORIENTATION



SPECIFICATION

INSULATOR MATERIAL:

THERMOPLASTIC

FLAMMABILITY RATING:

UL 94V-0

INSULATION RESISTANCE

5000M Ω MN.

PER MIL-STD-1344A METHOD 3003.1

OPERATING TEMP. RANGE:

-40°C TO + 105°C

DIELECTRIC STRENGTH:

600VAC MN.

PER MIL-STD-1344A METHOD 3001.1

CONTACT MATERIAL:

COPPER ALLOY

CURRENT RATING:

1A

CONTACT RESISTANCE:

30m Ω MAX.

PER MIL-STD-1344A METHOD 3002.1

RETENTION FORCE:

300g MN.

PER MIL-STD-1344A METHOD 2007.1

SOLDERABILITY:

PER MIL-STD-202F METHOD 208D

MATING OPTIONS

S10X SERIES.....DA~DG

ORDERING INFORMATION

S20X - 0100 - XX X
a b c

a: PACKAGING & CAP

* Q TUBE

2 TAPE & REEL (Limited availability)

b: NUMBER OF CONTACTS

08~36 40~52 56 60 64

68~72 80 84 88 90 100 (100 = AO)

c: CONTACT PLATING

SELECTED GOLD PLATING

* 1. G/F ALL OVER

* 6 G/F ON CONTACT AREA

7. 1 μ " ON CONTACT AREA

9. 3 μ " ON CONTACT AREA

