



EXCELLENCE IN CONNECTIVITY SOLUTIONS SCHWEIZ

DATUM MI, 22-MÄRZ-2006 15:48:30

DRUCKEN

FENSTER SCHLIESSEN

RF PRINT CONNECTORS - PRODUCT DATA

[New search](#)

Details

 Jump to [\[Mechanical data\]](#) [\[Electrical data\]](#) [\[Environmental data\]](#) [\[Material\]](#)

Item description 82_MCX-50-0-17/111_NH

Connector Description Straight PCB jack

Series / Pattern • MCX – Type / [Pattern 82](#)

Highlights • PCB connector without stand-offs



Item number 23000567

Outline drawing [82_MCX-50-0-17/111_N](#)

Catalogue drawing [82_MCX-50-0-17/111_N](#)

2002/95/EC (RoHS) compliant

Interface Standards IEC 60169-36; CECC 22220

Mechanical data

[Jump to \[Top\]](#)

Engagement Force max	25 N
Disengagement F. min	8 N
Disengagement F. max	20 N
Board Mounting Type	Through holes
Number of Printlegs	4
Printleg Length HL	4 mm
Height above PCB HA	6 mm
Height of Stand Off HS	0 mm

Electrical data

[Jump to \[Top\]](#)

Impedance	50 Ω
Interface Freq max	≤ 6 GHz

Environmental and general data

[Jump to \[Top\]](#)

Operating Temp min	-65 °C
Operating Temp max	165 °C
Weight	0.0007 kg
Number of Matings	500

Material

[Jump to \[Top\]](#)

2002/95/EC (RoHS) compliant

Piece part	Base material	Plating
Center contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer contact	Brass	Gold Plating (Nickel underplated)
Insulator	PFA / PTFE	
Body	Brass	Gold Plating (Nickel underplated)

.....
[Privacy policy](#) | [Haftungsausschluss](#) © 2005 HUBER+SUHNER