

Relays
➡ Industrial Relays (General Purpose)

P&B T92P11D22-12  [Active](#)

[Not ELV or RoHS Compliant](#)

(Tyco Electronics P/N: 5-1393211-3)

[Search for Compliant \(Leadfree\)
Alternative](#)

Searchable Features:	
Brand:	P&B
RoHS/ELV Compliance:	Non-compliant
Lead Free Solder Process:	Not relevant for lead free process
Series:	T92
Contact Arrangement:	2 Form C, DPDT, 2 C/O
Contact Current Rating (Amps.):	30
Coil Magnetic System:	Monostable
Coil Suppression Diode:	Without
Coil Selection Criteria:	Nominal Voltage
Coil Resistance (Ω):	86
Actuating System:	DC
Coil Latching:	No
Coil Power, Nominal (W):	1.70
Mounting Options:	Flange Mount
Termination Type:	.250 x .032 Quick Connect Terminals
Input Voltage (VDC):	12
Enclosure:	Dust Cover
FCC Part 68 Isolation:	No
Relay Type:	PCB
LED Indicator:	Without
Contact Material:	Silver Cadmium Oxide

Other Properties:	
Approx. Dimensions (L x W x H) (mm [in]):	52.30 x 34.50 x 30.70 [2.060 x 1.359 x 1.209]
Coil Insulation Classification:	UL Class F
Polarized:	No
Wiring Diagram:	2 Form C
Approved Standards:	UL Recognized, UL Listed, CSA Certified, CSA Component Acceptance, VDE Component Mark

